

Chemsorb® 620



High-grade impregnated activated carbon for removal of airborne ammonia and amines.

Description

Chemsorb® 620 is specifically designed as a high-grade impregnated activated carbon for use in critical filtration applications such as breathing air respirators. The proprietary reagent used to impregnate this high activity coconut shell carbon has shown superior results for the adsorption of airborne ammonia and amines. Chemsorb® 620 is virtually dust-free, ammonia-free, and contains no heavy metals such as copper, lead, mercury, nickel or chromium.

Typical properties

Test method

Carbon base	Granular coconut-shell	
Activity, CCl ₄ *	60, 70, or 85% minimum	ASTM D3467
Hardness, ball-pan	95 minimum	ASTM D3802
Ash content	5% maximum	ASTM D2866
Apparent density	0.59-0.64 g/ml	ASTM D2854
Surface area*	1000 m ² /g minimum	N ₂ BET method
Moisture content, as packed	9-12%	ASTM D2867

* Indicates properties of activated carbon prior to impregnation

Standard mesh sizes (US Sieve)

Molecular Products Ltd. designation	Particle size	ASTM D2862
G1	4 × 8	
G2	6 × 12	
G3	8 × 16	
G5	20 × 50	
G12	12 × 20	

Particle size distribution

Oversize maximum	5%
Nominal mesh size	90% minimum
Undersize maximum	5%

Note: This spec sheet indicates physical properties that are standard and typical. Molecular Products Ltd. will meet custom specifications as required.

Molecular Products Limited

Mill End, Thaxted, Essex
CM6 2LT United Kingdom

T +44 (0)1371 830676
F +44 (0)1371 830998

E sales@molprod.com
W www.molecularproducts.com

Doc.: 70
Rev.: D 03/12/09