

# Chemsorb® 620

High-grade impregnated activated carbon for removal of airborne ammonia and amines.



molecular

## Description

Chemsorb® 620 is specifically designed as a high-grade impregnated activated carbon for use in critical filtration applications such as breathing air respirators. The proprietary reagent used to impregnate this high activity coconut shell carbon has shown superior results for the adsorption of airborne ammonia and amines. Chemsorb® 620 is virtually dust-free, ammonia-free, and contains no priority pollutant metals such as copper, lead, mercury, nickel or chromium.

## Typical properties

## Test method

<b>Carbon base</b>	Granular coconut-shell	
<b>Activity, CCl<sub>4</sub>*</b>	60, 70, or 85% minimum	ASTM D3467
<b>Hardness, ball-pan</b>	95 minimum	ASTM D3802
<b>Ash content*</b>	5% maximum	ASTM D2866
<b>Apparent density (Dry)</b>	0.54-0.66 g/ml**	ASTM D2854
<b>Surface area*</b>	1000 m <sup>2</sup> /g minimum	N <sub>2</sub> BET method
<b>Moisture content, as packed</b>	9-13%	ASTM D2867

\* Indicates properties of activated carbon prior to impregnation

\*\*This density range is based on a 70% Activity level and a 12 x 20 particle size. The density values for other activity levels and particle sizes will differ.

## Standard mesh size (US Sieve)

<b>Molecular Products Inc. designation</b>	<b>Particle size</b>	ASTM D2862
<b>G5</b>	20x50	
<b>G12</b>	12x20	

## Particle size distribution

<b>Oversize maximum</b>	5%
<b>Nominal mesh size</b>	90% minimum
<b>Undersize maximum</b>	5%

Note: this technical datasheet indicates physical properties that are standard and typical. Molecular Products Inc. will meet customer specifications as required.

## Molecular Products Inc.

633 CTC Blvd Suite 200  
Louisville, CO 80027

**T** (303) 666 4400  
**F** (303) 665 0563

**E** infousa@molprod.com  
**W** www.molecularproducts.com

Doc. No. 70 Rev. F