

HiCap™ CO

Moleculite® carbon monoxide large absorber cartridge.



Introduction

The HiCap™ CO large scale absorber cartridges is for the removal and control of toxic **carbon monoxide** (CO). The units are designed to seal against the base plate cut-out of fan driven air supply equipment.

DO NOT remove the barrier foil packaging until immediately before the unit is to be used.

Operating instructions: carbon monoxide (CO)

1. Remove outer foil barrier film (a pair of scissors or sharp safety blade will be required).
2. Check that the bases seal is in place and intact, then place the unit onto the base unit aperture(s).
3. **Warning - all the base (fan) unit apertures must have cartridges installed for correct operation** - If the base unit has more than one aperture ensure all the apertures are covered with installed cartridges - use an exhausted cartridge if fresh cartridges are not available.
4. Start the airflow through the cartridge(s) - refer to the systems operating procedure.
5. In a multi-aperture base unit, if the some units are exhausted and fresh ones are not available the exhausted units should be left in place - used HiCap™ CO will continue to remove trace (<50ppm) concentrations of carbon monoxide for some time after the specified performance period so can be left in service provided power is available for this purpose.

Sufficient cartridges need to be available to provide carbon monoxide control from the highest expected concentration down to safe levels in an acceptable time. Self contained respirator sets may be required to maintain clean breathing air for the time that the carbon monoxide is being removed. Refer to the HiCap™ CO user manual or equipment manufacturer's manual for correct use of the system.

Storage, Maintenance and Condition checks.

The units do not require any maintenance in storage but do need to be stored in such a way that the barrier foil packaging prevents moisture or contamination entering the unit.

- The units need to be handled and stored under conditions that prevent damage to the barrier foil packaging i.e. avoid sharp objects or pressure points puncturing the packaging.
- The units should be stored between 0 - 35C°, out of direct sunlight and protected from wet conditions.
- Each unit is marked with a label on the outside of the packaging that shows the original packed weight of the unit. If the weight changes by more than the weight allowed and shown on the label, then unit should be replaced.

The units gain weight due to moisture adsorption (approximately 1 kg) in normal use, therefore if a unit is weighted, the label copy on the side of the cartridge itself can be used to check if unit have been used after it has been removed from its original packaging.

Conditions of use and limit of liability - HiCap™ - CO Molecularite filled large absorber cartridge

The units are designed to be used as part of a purpose built air purification system that can operate within the documented design parameters. No liability or guarantee of performance can be accepted for units operated outside these conditions.

The performance is guaranteed only if the units are used and stored within the declared operational limits set by the manufacturer and documented in the HiCap™ CO User Manual.

The units are supplied in a sealed barrier foil bag. The seal **must not be broken** until the unit is required for use as the unit absorbs water from the atmosphere that will slowly reduce its CO removal performance. The performance of units that have been opened, but not used, for more than a few hours in a moist environment cannot be guaranteed or predicted.

Units with damage to the sealed packaging should not be used. The units are supplied with a weight check and weight tolerance label that allows the user to establish if the units have remained sealed prior to use. The use of units that have failed this weight check requirement or that have damaged packaging cannot be guaranteed by the manufacturer as the performance may be affected.

The way that the units are used is the responsibility of the user and /or facility operator. It is strongly recommended that the facility operator should carry out a risk assessment of the way in which the unit(s) are to be used before they are deployed.

The units comply with the essential safety requirements of the EU Mechanical Directive and are labelled accordingly.